



PROTO Multi-Bit Screwdriver: Hex/Phillips/Slotted Tip, 11 Tips, 8 3/4 in Overall Lg, Magnetic, J9322

Mfr. Model J9322

Product Details

|                        |                                                                                  |                     |                                                                                                                              |
|------------------------|----------------------------------------------------------------------------------|---------------------|------------------------------------------------------------------------------------------------------------------------------|
| Brand                  | PROTO                                                                            | Finish              | Chrome                                                                                                                       |
| Tip Size               | #1; #2; 1/4 in; 11/32 in; 3/16 in; 5/16 in; 5/32 in; 7/16 in; 9/32 in; SL3/16 in | Corrosion Resistant | Corrosion-Resistant                                                                                                          |
| Tip Style              | Hex; Phillips; Slotted                                                           | For Screw Type      | Hex; Phillips; Slotted                                                                                                       |
| Bit Retainer Type      | Magnetic                                                                         | Handle Type         | Fluted                                                                                                                       |
| Grip Style             | Plain                                                                            | Handle Material     | Plastic                                                                                                                      |
| Bit Material           | S2 Steel                                                                         | Number of Bits      | 11                                                                                                                           |
| Bit Storage            | In Handle                                                                        | Number of Tips      | 11                                                                                                                           |
| Single/Double End Bits | Single End                                                                       | Number of Pieces    | 12                                                                                                                           |
| Magnetized Tip         | Magnetized Tip Included                                                          | Overall Length      | 8-3/4 in                                                                                                                     |
| Shank Material         | Alloy Steel                                                                      | Measurement Type    | SAE                                                                                                                          |
| Drive Size             | 1/4 in                                                                           | Sizes Included      | Nut Driver: Hex 3/16 in + 1/4 in + 9/32 in + 5/16 in + 11/32 in + 7/16 in<br>Phillips: #1 + #2<br>Slotted: 5/32 in + 3/16 in |
| ESD Safe               | Not ESD Safe                                                                     | Length Type         | Long Length                                                                                                                  |
| Insulated              | Not Insulated                                                                    | Series              | Proto                                                                                                                        |
| Ratcheting             | Ratcheting Included                                                              | UNSPSC              | 27112814                                                                                                                     |
| Replaceable Shank      | Fixed Shank                                                                      | Country of Origin   | USA                                                                                                                          |
| Tether Ready           | Not Tether Capable                                                               |                     |                                                                                                                              |